



PipeSak® Pipeline Protection

Technical Notes

PipePillo® Dimensional Data

PipePillo® Model		SPP8	SPP16	SPP24	SPP24	SPP36	SPP48
Pipe Size (in)		Up to 4"	Up to 8"	Up to 16"	Up to 24"	Up to 36"	Up to 48"
Weight	lbs. (kg)	0.8 (0.4)	0.8 (0.4)	5.1 (2.3)	9.2 (4.2)	26.7 (12.1)	42.8 (19.4)
Diameter (A)	in (cm)	9 (22.8)	9 (22.8)	16 (40.6)	24 (60.9)	36 (91.4)	46 (116.9)
Overall Height (B)	in (cm)	3.3 (8.4)	3.3 (8.4)	8 (20.3)	9.4 (23.8)	14.0 (36.0)	15.5 (39.4)
Low Stacked Height (C)	in (cm)	1.5 (3.8)	1.5 (3.8)	2.75 (7)	2.75 (7)	3 (7.6)	3 (7.6)
High Stacked Height (D)	in (cm)	N/A	N/A	4.5 (11.4)	4.5 (11.5)	6 (15.2)	6 (15.2)
Pipe Support Height (E)	in (cm)	2.5 (6.4)	2 (5.1)	6 (15.2)	6 (15.2)	8 (20.3)	8 (20.3)
Angle of Pipe Supported at Maximum Pipe Diameter		91.1°	98.5°	83.7°	88.7°	95.5°	90.2°

Notes: PipePillo® pipeline supports can be stacked in a stable extended mode (dimension 'D') to allow for use out of the trench as a pipe support during the stringing and welding process. When stacked, PipePillo® capacities are substantially reduced. Please contact PipeSak® for revised and required spacing.

